

ZEPHIR S



MINING & QUARRIES

Evacuation and material handling
hoses



APPLICATIONS

For suction of light industrial debris and dust.

Suitable for conveying small particles and moderately abrasive materials.

ADVANTAGES

- ¹ Very light weight and easy to handle.
- ¹ Excellent bending radius and flexibility.
- ¹ Very good crush resistance.

TECHNICAL DESCRIPTION

Inner tube: wear resistant NR, beige, smooth.

Reinforcement: synthetic textile, cords, with embedded steel helix.

Cover: rubber coated fabric, white, corrugated.

Temperature range: -30°C to +70°C.



**MINING & QUARRIES****ZEPHIR S**

ID mm	WALL THICKNESS mm	OD mm	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (1) or min. order m
30.0 ±1.5	4.5 ±0.75	39.0 ±1.5	0.8	150	0.5	10	0126702	20
35.0 ±1.5	4.5 ±0.75	44.0 ±1.5	0.8	175	0.57	10	0123919	10
40.0 ±1.5	4.5 ±0.75	49.0 ±1.5	0.8	200	0.63	10	0074118	20
50.0 ±1.5	4.5 ±1.0	59.0 ±2.0	0.8	250	0.79	10	0201844	1
60.0 ±1.5	4.5 ±1.0	69.0 ±2.0	0.8	300	0.9	10	0201845	20
70.0 ±1.5	4.5 ±1.0	79.0 ±2.0	0.8	350	1.02	10	0074130	20
80.0 ±1.5	5.5 ±1.0	91.0 ±2.0	0.8	400	1.46	10	0201846	1
100.0 ±1.5	5.5 ±1.0	111.0 ±2.0	0.8	500	1.79	10	0201847	1
105.0 ±1.5	5.5 ±1.0	116.0 ±2.0	0.8	525	1.84	10	0070668	20
115.0 ±1.5	5.5 ±1.0	126.0 ±2.0	0.8	575	2	10	0070553	20
125.0 ±1.5	5.5 ±1.0	136.0 ±2.0	0.8	625	2.23	10	0095689	1
150.0 ±1.5	7 ±1.0	164.0 ±2.0	0.8	750	3.76	10	0202128	1

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version



WWW.TRELLEBORG.COM/FLUIDHANDLING