

TRELLJET 681 AP



FOOD & BEVERAGE

Food industry High pressure jetting



APPLICATIONS

Specially designed for professional and industrial high pressure cleaning.

The antimicrobial TRELLJET 681 is suitable for all environments where bacteria are concerned: cleaning companies, food industries, pharmaceutics, packaging/bottling, health care institutions, schools, etc.

Suitable for mobile pressure washers, fixed installations and reel mounted applications.

ADVANTAGES

- Crush resistant.
- Antimicrobial protection: prevents odor, stain, degradation and breakdown from bacterial attacks.
- Non-staining smooth cover.
- Oil, detergents, wear and weather resistant.
- High temperature resistance.
- Highly flexible and kink resistance.
- Long service life.

TECHNICAL DESCRIPTION

Inner tube: NBR/SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: NBR/SBR, blue, smooth.

Temperature range: -40°C to +120°C.

Special properties: Antimicrobial protection in reference to:

- ISO 22196 (Quantitative analysis of bacterial growth).
- AATCC 30 (Qualitative analysis to evaluate the antimicrobial activity of fungicides).

COUPLINGS/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

COMPLEMENTARY INFORMATION

Available in random lengths: 20-95m. 50% of the volume in each delivery will be random lengths, shortest length of 20m, at least 50% will be in fixed length mentioned in the table.

ND 10mm







À	FOOD & BEVERAGE		TRE	ILLJET 681 AP						
I D mm	WALL THICKNESS mm	OD mm	REINF. DIAMETER mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	MAX. LENGTH m	ARTICLE NUMBER	STOCK (:) or min. order m
9.5 +0.6 - 0.2	4.5	18.5 ±0.8	15 ±0.3	200	500	60	0.29	95	5603263	¤
9.5 +0.6/-0.2	4.5	18.5 ±0.8	15 ±0.3	200	500	60	0.29	100	5603183	I
12.7 +0.8 -	4.5	21.7 ±0.6	18.3 ±0.3	200	500	70	0.4	95	5603264	¤
12.7 +0.8/-0.4	4.5	21.7 ±0.8	18 ±0.3	200	500	70	0.4	100	5603184	ı
Tolerance on length: ±1% (ISO 1307 Standard).										

Digital version



